Dorado
20’ x 20’ Truss System
UV Printed

TEMPLATE SET-UP AT 1/2 SCALE

Panels DO1-A, DO4-A, DO1-B, DO4-B, DO1-C, DO4-C, DO1-D, DO4-D:
Total Graphic Area: 80.375”w x 38.75”h
Finished Size: 79.375”w x 37.75”h

Panels DO2-A, DO2-B, DO2-C, DO2-D:
Total Graphic Area: 50”w x 38.75”h
Finished Size: 49”w x 37.75”h

Panels DO3-A, DO3-B, DO3-C, DO3-D:
Total Graphic Area: 50”w x 84.75”h
Finished Size: 49”w x 83.75”h

Panels DO5-A, DO8-A, DO5-B, DO8-B, DO5-C, DO8-C, DO5-D, DO8-D:
Total Graphic Area: 80.375”w x 38.75”h
Finished Size: 79.375”w x 37.75”h

Panels DO6-A, DO6-B, DO6-C, DO6-D:
Total Graphic Area: 40.5”w x 38.75”h
Finished Size: 39.5”w x 37.75”h

Template requires 1/4” bleed around the perimeter (1/2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4” w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4” w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location. Indicated by a yellow square in the template.
Hinging= 3/4” strip of material that is cropped from the panel and reapplied with hinge tape. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color
- Do not embed images, supply them
- Resolution must be 200-240 ppi @ half size, 100-120 ppi @ full size
- All fonts must be created to outlines