
Formulate Wave Counter - 06

W-06-C-7

Formulate® counters couple lightweight hardware with state-of-the-art printed stretch silicone edge push-fit fabric graphics to create funky and functional reception stands.



features and benefits:

- Premium aluminum tube frames with cam lock assembly
- Easy to store and ship
- Counter top and base (come in a variety of colors)
- One push-fit fabric graphic

black

mahogany

natural


- Lifetime limited hardware warranty against manufacturer defects


dimensions:

dimensions:	
Hardware	Graphic
Assembled unit: 120"w x 37.8"h x 24"d 3048mm(w) x 960mm(h) x 610mm(d) Approximate weight with cases: 385 lbs / 175 kgs	Refer to related graphic template for more information. Visit: www.exhibitors-handbook.com/ graphic-templates
Shipping	additional information:
Packing case(s): OCH2 x4	Graphic material: dye-sublimation push-fit fabric graphic
Shipping dimensions: 52"l x 30"w x 14"h 1321mm(l) x 762mm(h) x 356mm(d) Approximate total shipping weight (includes cases & graphics): 418 lbs / 190 kgs	Counter top Dimensions: 120"w x 1.18"h x 24"d Inside Radius 2' Outside Radius 5' Counter top Max Weight Capacity: 45 lbs.
	Wood Finish Options

We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.


Included In Your Kit





Exploded View

W-06-C-7



Kit Assembly


Step by Step

Step 1.

Locate your counter bases and position them together. Lock them together using the locking mechanisms on the top side of the bases. You will need your 10mm allen key to do so.

Reference the Exploded View for more information.





Step 2.

Locate your triangular truss and fastening hardware. Hand tighten the truss onto the bases. Locate your silicone edge graphic. Push the silicone edges into the grooves of the counter base assembly.

Reference the Exploded View for more information.






Step 3.

Locate your counter tops and fastening hardware. Starting from one end, hand tighten the truss on to the counter tops and lock them together using your 10mm allen key.

Reference the Exploded View for more information.





Step 4.

Pull up your silicone edge graphic. Push the silicone edges into the grooves of the counter top assembly.

Setup is complete.

